


THE Be-Mo (BERYLLIUM-MOLYBDENUM) SYSTEM

H. Okamoto
L. E. Tanner

This paper was prepared for submittal to
Bulletin of Alloy Phase Diagrams

April 18, 1986



This is a preprint of a paper intended for publication in a journal or proceedings. Since changes may be made before publication, this preprint is made available with the understanding that it will not be cited or reproduced without the permission of the author.

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial products, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

The Be-Mo (Beryllium-Molybdenum) System
9.01218 95.94

By H. Okamoto and L.E. Tanner
Lawrence Livermore National Laboratory

Equilibrium Diagram

[73Goll] tentatively composed the Be-Mo phase diagram from various results reported in [Hansen] and [Elliott]. Thermodynamic modeling by [80Brel] nearly reproduced the diagram of [73Goll], with only significant change in the extended stability of Be_{22}Mo at low temperatures. The assessed diagram (Fig. 1) is primarily adopted from [80Brel], with some modification based on experimental observations.

There are four intermediate phases reported for this system: (1) Be_{22}Mo (Zn₂₂Zr-type); (2) Be_{12}Mo (Mn₁₂Th-type); (3) Be_2Mo (MgZr₂-type); and (4) BeMo_3 (Cr₃Si-type). The melting points and the homogeneity ranges for all phase compounds have not been well established.

(β Be) and (α Be) Terminal Solid Solutions. The melting point of β Be and the β Be \rightarrow α Be allotropic transformation temperature are 1289 \pm 4 and 1270 \pm 6 $^{\circ}\text{C}$, respectively [86BAP]. The reaction type between (β Be) and (α Be) and the solubility limits of Mo in these terminal solid solutions have not been reported.

(Mo) Terminal Solid Solution. The melting point of Mo is 2623 $^{\circ}\text{C}$ [Melt]. The Mo solvus was deduced from hardness measurements by [51Ham]:

Temperature, $^{\circ}\text{C}$	at.% Be
eutectic	0.53
1740	0.42
1480	0.2

Earlier, [50Ham] estimated the solubility limit of Be in (Mo) to be about 0.9 at.%. A eutectic structure composed of (Mo) plus Be_2Mo was observed beyond the solid solubility [50Ham, 50Kaul]. The eutectic composition is at approximately 57 at.% Mo according to microstructural examinations [51Ham]. Observations of incipient melting by [51Ham] placed the eutectic temperature slightly below 1870 $^{\circ}\text{C}$. [80Brel] estimated this temperature to be at 1827 \pm 50 $^{\circ}\text{C}$.

Be_{22}Mo . The existence of and the formula for this compound were established by [61Boo], [62Mat], [63Kri], and [64Mat], replacing earlier tentative stoichiometries of Be_{20}Mo [59Arz1, 59Arz2] and Be_{20}Mo [60Pail]. Diffusion studies suggested the existence of this phase at temperatures between 1050 and 1200 $^{\circ}\text{C}$, but not at 950 $^{\circ}\text{C}$ [59Arz1] nor at room temperature [60Zal].

The superconducting transition temperature of Be_{22}Mo has been reported to be 2.51 K by [67Buc] and 2.545 K by [73Mat].

Be_{12}Mo . This phase was initially identified as Be_{13}Mo by [36Mis] and [51Gor]. The more satisfactory stoichiometry was determined by [51Ham] and later confirmed by many other investigators, viz. [55Rae], [57Gla], [58Che], [59Arz2], [60Zal], [62Mat], [64Mat], and [65Bea]. The melting point is approximately 1700 °C [60Sto].

Be_2Mo . This phase was first observed by [36Mis], and subsequent reports by [51Gor], [59Pai], [60Zal], [62Mat], and [64Mat] confirmed its existence. The melting point (T_m) of Be_2Mo was set at 1840 °C by [59Pai]. The thermodynamic model by [80Bre] places T_m at a somewhat higher temperature (2027±200 °C), as [73Gol] assumed, in order to be consistent with the observed $L \rightarrow \text{Be}_2\text{Mo} + (\text{Mo})$ eutectic point.

The superconducting transition temperature for Be_2Mo is 1.68 K [73Mat].

BeMo_3 . This phase was reported by [59Pai] and believed to melt at >1650 °C. However, this compound must decompose by a solid state reaction at a high temperature in order to be consistent with presence of the established eutectic between (Mo) and Be_2Mo . [80Bre] estimated a peritectoid reaction with a temperature at 900±100 °C. We have indicated this reaction to be at 1650 < T < 1827 °C.

Metastable Phase

[80Tan] predicted the possible existence of a metastable phase, BeMo , having the CsCl-type crystal structure from the study of a series of Be-transition metal systems.

Crystal Structures

A summary of crystal structure and lattice parameter data is given in Table 1. The mean linear thermal expansion coefficient of Be_{12}Mo was measured by [65Bea].

Mean linear thermal expansion coefficient
of Be_{12}Mo [65Bea].

Temperature, °C	α , $\times 10^{-6} \text{m/m/}^\circ\text{C}$
27 to 316	12.1
27 to 982	15.1
27 to 1482	16.7

Thermodynamics

[80Bre] calculated a Be-Mo phase diagram (Table 2) based on estimated thermodynamic functions for various Be-Mo phases as given in Table 3. His calculated liquidus boundaries are accepted in Fig. 1. The Be_{22}Mo and the BeMo_3 phases were proposed to be stable below 1300 and 900±100 °C,

respectively. The low-temperature instability of Be₂Mo in Fig. 1 is, however, based on experimental observations.

Cited References

- *36Mis: L. Misch, "Crystal Structures of Some Beryllium Alloys," Metallwirtschaft, **15**(6), 163-166 (1936). (Equi Diagram, Crys Structure; Experimental)
- 50Ham: J.L. Ham, "Arc-Cast Molybdenum-Base Alloys," Climax Molybdenum Company of Michigan, Annual Report, 031-331, 164pp (1950). (Equi Diagram; Experimental)
- 50Kau: A.R. Kaufmann, P. Gordon, and D.W. Lillie, "The Metallurgy of Beryllium," Trans. ASM, **42**, 785-844 (1950). (Equi Diagram; Experimental)
- 51Gor: S.G. Gordon, J.A. McGurty, G.E. Klein, and W.J. Koshuba, "Intermetallic Compounds in the system Molybdenum-Beryllium," Trans. Met. Soc. AIME, **191**, 637-638 (1951). (Equi Diagram, Crys Structure; Experimental)
- *51Ham: J.L. Ham, "Arc-Cast Molybdenum-Base Alloys," Climax Molybdenum Company of Michigan, Annual Report, 034-401, (1951). (Equi Diagram; Experimental; #)
- *55Rae: R.F. Raeuchle and F.W. von Batchelder, "The Structure of MoBe_{1,2}," Acta Crystallogr., **8**, 691-694 (1955). (Equi Diagram, Crys Structure; Experimental)
- 57Che: Ye.Ye. Cherkashin, Ye.I. Gladyshevskii, and P.I. Kripyakevich, "Compounds of the Transition Metals with Beryllium, Silicon, Germanium, and Tin," Dopovidi Lvivsk. Derzh. Univ., **7**(3), 180-183 (1957) in Russian. (Crys Structure; Experimental)
- 57Gla: E.I. Gladyshevskii and P.I. Kripiakevich, "Crystal Structure of the Compounds MoBe_{1,2}, WBe_{1,2} and TaBe_{1,2}," Kristallografiya, **2**, 742-745 (1957) in Russian; TR: Sov. Phys. Crystallogr., **2**, 730-733 (1957). (Equi Diagram, Crys Structure; Experimental)
- 58Che: Ye.Ye. Cherkashin, Ye.I. Gladyshevskiy, P.I. Kripyakevich, and Yu.B. Kuz'ma, "X-ray Structural Analysis of Certain Systems of Transition Metals," Zh. Neorgan. Khim., **3**(3), 650-653 (1958) in Russian; TR: Russ. J. Inorg. Chem., **3**(3), 135-141 (1958). (Equi Diagram, Crys Structure; Experimental)
- 59Arz1: P.M. Arzhanyi, "Character Change in the Microhardness Structures in the Molybdenum-Beryllium and Molybdenum-Aluminum Systems," Issled. po Zharoproch. Splavam, Akad. Nauk SSSR, **4**, 343-345 (1959) in Russian. (Equi Diagram; Experimental)
- 59Arz2: P.M. Arzhanyi, "Phase Composition of the Diffusion Layer of Beryllium in Molybdenum," Issled. po Zharoproch. Splavam, Akad. Nauk SSSR, Inst. Met., **5**, 199-202, (1959) in Russian. (Equi Diagram, Crys

Structure; Experimental)

- *59Pai: R.M. Paine, A.J. Stonehouse, and W.W. Beaver, "An Investigation of Intermetallic Compounds for Very High Temperature Applications," WADC Tech. Rept. 59-29 (1959). (Equi Diagram; Experimental)
- *60Pai: R.M. Paine and J.A. Carrabine, "Some New Intermetallic Compounds of Beryllium," Acta Crystallogr., 13, 680-681 (1960). (Equi Diagram, Crys Structure; Experimental)
- 60Sto: A.J. Stonehouse, R.M. Paine, and W.W. Beaver, "Mechanical Properties of Some Transition Element Beryllides," in Mechanical Properties of Intermetallic Compounds, J.H. Westbrook (ed.), John Wiley & Sons, Inc., NY, 297-319 (1960). (Equi Diagram; Experimental)
- 60Zal: A. Zalkin and D.E. Sands, "Crystallography of Some of the Transition Element Beryllides," U.S. Atomic Energy Comm., UCRL-5988-T, 6pp, May 24 (1960). (Equi Diagram; Experimental)
- 61Boo: J. Bocker, R.M. Paine, and A.J. Stonehouse, "Investigation of Intermetallic Compounds for Very High Temperature Applications," Tech. Rept. WADD-TR-60-889 (AD 265625), 128 (1961). (Equi Diagram; Experimental)
- *62Mat: N.N. Matyushenko, L.F. Verkhorobin, N.S. Pugachev, and N.V. Sivokon', "The Crystal Structure of the Highest Beryllides of Molybdenum, Wolfram, and Rhenium," Krystallografiya, 7, 862-864 (1962) in Russian; TR: Sov. Phys. Crystallogr., 7, 701-703 (1963). (Equi Diagram, Crys Structure; Experimental)
- 63Kri: P.I. Kripyakevich and E.I. Gladyshevskii, "The Crystal Structures of Beryllium-Rich Compounds in the Systems Mo-Be and W-Be," Kristallografiya, 8, 449-451 (1963) in Russian; TR: Sov. Phys. Crystallogr., 8, 349-351 (1963). (Equi Diagram, Crys Structure; Experimental)
- 64Mat: N.N. Matyushenko, "Reactional Diffusion in Molybdenum-Beryllium Alloys," Izv. Akad. Nauk SSSR, Met. i Gorn. Delo., (2), 167-171 (1964) in Russian. (Equi Diagram; Experimental)
- 65Bea: W.W. Beaver, A.J. Stonehouse, and R.M. Paine, "Development of Intermetallic Compounds for Aerospace Applications," in Metals for the Space Age, Plansee Proceedings 1964, Fifth Plansee Seminar, (ed.) F. Benesovsky, Metallwerk Plansee Ag., Reutte/Tyrol (1965). (Crys Structure; Experimental)
- 67Buc: E. Bucher and C. Palmy, "Superconductivity and Isotope Effect in Be₂X Compounds and Molybdenum," Phys. Lett., 24A, 340-341 (1967). (Equi Diagram; Experimental)
- 73Gol: O. von Goldbeck, "Phase Diagrams," in Beryllium: Physico-Chemical Properties of Its Compounds and Alloys, Atomic Energy Review: Special Issues, No. 4, 45-61, (ed.) O. Kubaschewski, UNIPUB, New York (1973). (Equi Diagram; Review; #)

73Mat: N.N. Matyushenko, A.A. Matsakova and N.S. Pugachev, "Superconductivity of Some Transition Metal - Beryllium Compounds," Ukr. Fiz. Zh., 18(4), 672-675 (1973) in Russian. (Equi Diagram; Experimental)

75Stu: M. Stunke and G. Petzow, "Crystal Structure and Lattice Constants of Transition Metal-Diberyllides and Diborides in Ternary Solid Solutions," Z. Metallkd., 66(5), 292-297 (1975) in German. (Crys Structure; Experimental)

*80Bre: L. Brewer, R.H. Lamoreaux, R. Ferro, R. Marazza, and K. Girgis, Molybdenum: Physico-Chemical Properties of Its Compounds and Alloys, Atomic Energy Review, Special Issue No. 7, International Atomic Energy Agency, Vienna (1980). (Equi Diagram, Thermo; Theory; #)

80Tan: L.E. Tanner, "The Stable and Metastable Phase Relations in the Hf-Be Alloy System," Acta Metall., 28(12), 1805-1816 (1980). (Meta Phases; Theory)

84Col: D.M. Collins and M.C. Mahar, "The Redetermination of the Structure of Beryllium-Molybdenum $\text{MoBe}_{1.2}$," Acta Crystallogr., C40(6), 914-915 (1984).. (Crys Structure; Experimental)

86BAP: to be published in Bull. Alloy Phase Diagrams, (1986). (Equi Diagram; Compilation)

* Indicates key paper.

Indicates presence of a phase diagram.

Acknowledgments

Be-Mo evaluation contributed by L.E. Tanner, L-217, Lawrence Livermore National Laboratory, P.O. Box 808, Livermore, CA 94550 and H. Okamoto, B77G, Lawrence Berkeley Laboratory, Berkeley, CA 94720. Work was supported by the U.S. Department of Energy under contract no. W-7405-Eng-48 and American Society for Metals (ASM). Literature searched through 1984. Part of the bibliographic search was provided by ASM. L.E. Tanner and H. Okamoto are ASM/NBS Data Program Category Editors for binary beryllium alloys.

Table 1 Be-Mo Crystal Structure and Lattice Parameter Data

Phase	Composition, at.% Mo	Struktur- Pearson bericht		Space group	Proto- type	Lattice parameters, nm		Reference
		symbol	designation			a	c	
(β Be)....	0	cI2	A2	Im3m	W	0.25515	...	[82Kin]
(α Be)....	0	hP2	A3	P6 ₃ /mmc	Mg	0.22857	0.35839	[81Kin]
Be ₂₂ Mo...	4.3	cF184	...	Fd3m	Zn ₂₂ Zr	1.1636	...	[62Mat]
						1.1634	...	[63Kri]
Be ₁₂ Mo...	7.7	tI26	D2 _h	I4/mmm	Mn ₁₂ Th	0.7271	0.4234	[55Rae]
						0.7255	0.4188	[57Che]
						0.7286	0.4242	[57Gla]
						0.7252	0.4232	[58Che]
						0.7285	0.4264	[59Arz2]
						0.7251	0.4234	[84Col]
Be ₂ Mo....	33.3	hP12	C14	P6 ₃ /mmc	MgZr ₂	0.4444	0.7290	[36Mis]
	32.89					0.4433	0.7341	[51Gor]
	33.27					0.4449	0.7298	[75Stu]
	33.33					0.4442	0.7294	
						0.4448	0.7310	
BeMo ₃	75	cP8	A15	Pm3n	Cr ₃ Si	0.489	...	[60Pai]
(Mo)....	100	cI2	A2	Im3m	W	0.31470	...	[81Kin]

Table 2 Phase Boundaries Estimated by [80Bre]

Boundary	Type	Expression
L/[L+(Mo)]	Liquidus	$X_{Be} = 5.84 \times 10^{-4}(2890-T) - 9 \times 10^{-10}(2890-T)^2 - 7.5 \times 10^{-11}(2890-T)^3 \pm 0.01$
[L+(Mo)]/(Mo)	Solidus	$X_{Be} = 1.86 \times 10^{-3}(2890-T) - 2.08 \times 10^{-8}(2890-T)^2 + 7 \times 10^{-12}(2890-T)^3 \pm 0.001$
(Mo)/[(Mo)+Be ₂ Mo]	Solvus	$X_{Be} = -11000/T \pm 0.1$
L/[L+Be ₂ Mo]	Liquidus (Mo-rich)	$X_{Be} = 0.425 + 1.09 \times 10^{-3}(T-2100) - 7.9 \times 10^{-6}(T-2100)^2 + 4.2 \times 10^{-9}(T-2100)^3 \pm 0.02$
L/[L+Be ₂ Mo]	Liquidus (Be-rich)	$X_{Be} = 0.991 - 1.5 \times 10^{-3}(T-1900) + 6.7 \times 10^{-6}(T-1900)^2 - 1.24 \times 10^{-9}(T-1900)^3 \pm 0.04$
L/[L+Be ₁₂ Mo]	Liquidus (at high X _{Be})	$\ln X_{Mo} = -9.64 + 2.7 \times 10^{-2}(T-1500) + 6.7 \times 10^{-6}(T-1500)^2 + 7.9 \times 10^{-9}(T-1500)^3 \pm 0.02$

X in atomic fraction. T in K.

Table 3 Thermodynamic Data Estimated by [80Brel]

For $\text{Mo(l)} = \text{Mo(liq. soln.)}$

$$\bar{G}^{\infty}/RT = (0.5 - 2060/T)X_{\text{Be}}^2 \pm 0.3 \quad (1300 \text{ to } 2890 \text{ K})$$

and the corresponding equation for Be.

For $\text{Be(s)} = \text{Be(bcc Mo)}$

$$\bar{G}^{\infty}/RT = 8600/T \pm 0.2 \quad (2100 \text{ to } 2890 \text{ K})$$

For $\text{Be(s)} + 3\text{Mo(s)} = \text{BeMo}_3(\text{s})$

$$\begin{aligned} \Delta H_{298}^{\circ}/R &= -2200 \pm 2000 \text{ K} \\ (G^{\circ} - \Delta H_{298}^{\circ})/RT &= 0.9 \pm 0.5 \quad (298 \text{ to } 900 \text{ K}) \end{aligned}$$

For $2\text{Be(s)} + \text{Mo(s)} = \text{Be}_2\text{Mo(s)}$

$$\begin{aligned} \Delta H_{298}^{\circ}/R &= -3800 \pm 2000 \text{ K} \\ (G^{\circ} - \Delta H_{298}^{\circ})/RT &= 0.79 \pm 0.5 \quad (298 \text{ to } 2027 \text{ K}) \end{aligned}$$

For $22\text{Be(s)} + \text{Mo(s)} = \text{Be}_{22}\text{Mo(s)}$

$$\begin{aligned} \Delta H_{298}^{\circ}/R &= -13000 \pm 2000 \text{ K} \\ (G^{\circ} - \Delta H_{298}^{\circ})/RT &= -1 \pm 2 \quad (198 \text{ to } 1570 \text{ K}) \end{aligned}$$

